

Procedure to fix the creaking/popping removable top on a C6 Corvette (suggestion is to do this at least every two years):

1. Remove the [roof panel](#) from the car and set on a non- scratching surface.
2. Clean all of the weather stripping on the car and top with a foaming cleaner and microfiber towel
3. Torque all of the locating pins to 16 ft-lbs
4. Clean and lubricate the locating pins with dielectric grease
5. Remove your front latch handles and also lubricate the T40 shoulder bolt with dielectric grease
6. Reinstall the bolts and handles. Torque to 13 ft-lbs
7. Lubricate the weather strips with GM weather strip lubricant (expensive way) or Gummi Pflege (same concept but much less costly), allow to sit for 1 hour and then wipe off the excess
8. Reinstall your top and enjoy the quiet time behind the wheel of your C6!

**3634770 - GM/AC Delco Weatherstrip Lubricant, For Weatherstrips, Convertible Top Seal, T-Top Seals, Door Seals - 1 oz. \$59.62 at Amazon**

**OR:**

**EIN-914806 - Gummi Pflodge Stit Weatherstrip Lubricant, For Weatherstrips, Convertible Top Seal, T-Top Seals, Door Seals – 3.4 oz. \$8.99 at Autogeek.com**

**Video of the procedure is here:**

<http://www.corvetteblogger.com/2014/05/12/video-how-to-fix-a-creaky-removable-top-on-a-c6-corvette-coupe/>

--- Compiled by George P. – Corvette Legends Club

If your latch has the rollers you can also insert some Hillman's 5/32" e-clips (available at Lowes) on the pins of the rollers.



CLIP

